PRODUCT DATA SHEET

PRINCIPAL APPLICATIONS

Ultrapure Water

Purolite[™] UltraClean[™] UCW3700

Polystyrenic Gel, Gel, Mixed Bed Resin, Hydrogen form, Hydroxide form, Ultrapure Water Grade

SYSTEMS

Mixed bed demineralizer

REGULATORY APPROVALS

IFANCA Halal Certified

TYPICAL PACKAGING

- 1 CF Box
- 50 L Drum (Plastic)
- 5 ft³ Drum (Fiber)

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

| Appearance | Spherical Beads | |
|--|--|---|
| TOC (max.) | < 10 ppb TOC after 40 BV of rinse at 30 BV/h (*) | |
| Resistivity | > 18 MΩ cm after 15 BV rinse at 30 BV/h (*) | |
| Shipping Weight (approx.) | 685 - 725 g/L (42.8 - 45.3 lb/ft³) | |
| Temperature Limit | 60 °C (140.0 °F) | |
| Component Name | UltraClean Grade Gel Cation | UltraClean Grade Gel Type I Anion |
| Polymer Structure | Gel polystyrene crosslinked with divinylbenzene | Gel polystyrene crosslinked with divinylbenzene |
| Functional Group | Sulfonic Acid | Type I Quaternary Ammonium |
| Ionic Form | H ⁺ form | OH ⁻ form |
| Cation / Anion Chemical Equivalent Ratio | 1 | 1 |
| Total Capacity (min.) | 1.8 eq/L (H ⁺ form) | 1 eq/L (OH ⁻ form) |
| Mean Diameter | 610 ± 40 μm | 570 ± 50 μm |
| Conversion (min.) | 99.9 % (H ⁺ form) | 95 % (OH ⁻ form) |
| Moisture Retention | 49 - 54 % (H ⁺ form) | 60 - 70 % (OH ⁻ form) |
| Uniformity Coefficient | 1.2 | 1.2 |
| Footnote | * Influent rinse water quality : > 17.5 MΩ cm; < 2 ppb TOC | |
| | | |



Ecolab is a global developer, manufacturer, and supplier of Purolite™ Resins including ion exchange, catalyst adsorbent and advanced polymers that make the world cleaner and healthier.



www.puroliteresins.com



We're ready to solve your process challenges.

For further information on products and services, visit www.puroliteresins.com or complete a Contact Us form via PuroliteResins.com/contact-us or use the QR code.

Contact Us Form:



The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Purolite expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

